



City of Cerritos

Civic Center • 18125 Bloomfield Avenue
P.O. Box 3130 • Cerritos, California 90703-3130
Phone: (562) 916-1219 • Fax (562) 916-1211

EXCAVATION PERMIT SPECIAL PROVISIONS

Permit No. _____

1. A valid USA number shall be provided to the City 48 hours prior to starting work.
2. Lane reduction hours shall be from 9:00 A.M to 2:30 P.M. (on arterial streets). Solar-powered arrowboards shall be required for lane closures.
3. Permittee shall be responsible for repairing or replacing in like kind any public or private improvements damaged as a result of this permit.
4. Protect underground utilities shown or not shown on the plans.
5. Street repairs shall be made to match the existing, or as required by the City.
6. Trench repair shall be made per City Standard Plan No. S-D-25 or as required by the City.
7. Concrete pavement, curb and gutter shall be removed and replaced by sawcutting to the nearest score mark. All concrete improvements shall be constructed per American Public Works Association (Latest Edition) standards.
8. Potholes/ boring pits on A.C. pavement shall be repaired per requirement No.6 above.
9. Traffic warning devices shall be placed in accordance with "WATCH" manual and will be maintained at all times.
10. Permit shall be posted on the job at all times.
11. Permit shall be voided if work is not commenced within sixty (60) days after the date of issuance, unless otherwise specified.
12. Permit is valid for 6 months after the date of issuance unless otherwise specified.
13. When requesting inspection, permittee shall give the following information: a) valid USA number when excavating; b) location; c) time needed; d) date needed; e) contractor's name; and f) permit number.
14. Sidewalk shall remain clear to pedestrian traffic at all times.
15. Noise abatement shall be enforced at all times.

16. Twenty-four hour telephone numbers of responsible company officials shall be maintained within the City.
17. Permit to excavate or work in the PUBLIC RIGHT-OF-WAY is subject to provisions required by CAL OSHA Division of Industrial Safety and by City Ordinance No. 46, and amendments thereto.
18. Landscaping in parkway is to be fully restored to pre-excavation condition after construction.
19. When a trench in a traveled roadway is to be plated to permit vehicular traffic, the plates shall be coated with a non-skid material. The plates shall be pinned and ramped with temporary A.C. prior to opening the construction area to traffic.
20. No storage of materials or equipment shall be allowed overnight within the public right-of-way. A Temporary Use Permit (T.U.P) application must be made prior to the storage of any equipment or materials on private property within the Cerritos City limits.
21. Permittee shall implement storm water and urban runoff pollution prevention controls, and Best Management Practices (BMPs), on construction sites in accordance with Chapter 6.32 of the Cerritos Municipal Code (Ordinance No. 777). At a minimum, the attached Stormwater Pollution Prevention Notes must be implemented on the job at all times.
22. Notify Residents 48 hours prior to work.
23. Soil compaction and material testing, if required, shall be the contractor's responsibility and done at his/her expense.

Stormwater Pollution Prevention Notes

1. The Contractor shall be responsible to install, maintain, and inspect all stormwater pollution prevention devices.
2. A stand-by crew for emergency work shall be available at all times during the rainy season (October 1st through May 1st). Necessary materials shall be available onsite and stockpiled at convenient locations to facilitate rapid construction of emergency devices when rain is imminent.
3. Erosion control devices shown on this plan may be removed when approved by the grading inspector if the grading operation has progressed to the point where they are no longer required.
4. Eroded sediments and other pollutants must be retained on site and may not be transported from the site via sheet flow, swales, area drains, natural drainage courses or wind.
5. Stockpiles of earth and other construction-related materials must be protected from being transported from the site by the forces of wind and water flow.
6. Fuels, oils, solvents, and other toxic materials must be stored in accordance with their listing and are not to contaminate the soils and surface waters. All approved storage containers are to be protected from the weather. Spills must be cleaned up immediately and disposed of in a proper manner. Spills may not be washed into the drainage system, nor be allowed to settle or infiltrate into soil.
7. Excess or waste concrete may not be washed into the public way or any other drainage system. Provisions shall be made to retain concrete wastes on site until they can be disposed of as solid wastes.
8. Trash and construction solid wastes must be deposited into a covered receptacle to prevent contamination of rainwater and dispersal by wind.
9. Sediments and other materials may not be tracked from the site by vehicle traffic. The construction entrance roadways must be stabilized so as to inhibit sediments from being deposited into the public way. Accidental depositions must be swept up immediately and may not be washed down by rain or other means.
10. Any slopes with disturbed soils or removed vegetation must be stabilized to inhibit erosion by wind and water.
11. Erosion control devices will be modified as needed as the project progresses, at the direction of the City Engineer.